

**QUIK-Stick HT***High-temperature (smooth poly surface)*Uses & Description

QUIK-Stick HT is an SBS modified self-adhering membrane reinforced with non-woven fiberglass mat for extra strength and durability. It's non-abrasive polyester surface is excellent for use in tile and metal applications.

Benefits

- Offers a skid resistant, polyester surface.
- Silicone-treated, split-back, release film allows for easy installation and handling
- Softening point is a minimum of 250°F
- May be installed directly to concrete, plywood, wood composition board and gypsum
- Self seals around nails
- May be used in new construction or re-roofing
- Offers greater tear resistance than traditional felt underlayment
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers and skylights
- Provides excellent low temperature flexibility
- May be left exposed up to 90 days prior to application of finished roof
- Florida Approval (FL #13857)

Specifications

<b>ASTM</b>	D 1970
<b>Thickness, min</b>	60 mils
<b>Maximum Load, min</b>	MD=80 CD=40
<b>Elongation at Break, min</b>	30%
<b>Adhesion to Plywood @ 77 °F min</b>	30.0 lbf/ft
<b>Thermal Stability, max</b>	0.05
<b>Flexibility Temperature, @ -20 °F min</b>	pass
<b>Sealability around nail</b>	pass
<b>Water Proof Integrity after Low Temp. Flex</b>	pass
<b>Waterproof Integrity of lap Seam</b>	pass
<b>Slip Resistance</b>	pass
<b>Rolls per Pallet (label / box)</b>	25 / 20
<b>Roll Weight</b>	65 lbs ± 2lbs
<b>Roll Diameter</b>	8.5 in.
<b>Square feet</b>	200
<b>Available roll dimensions</b>	36" x 66.8' (200sqft)