

### QUIK-Stick VFS2

Valleyfast

#### Uses & Description

QUIK-Stick Valleyfast is an SBS modified self-adhering membrane reinforced with non-woven fiberglass mat for extra strength and durability. QUIK-Stick Valleyfast is a highly versatile underlayment that provides superior waterproof integrity and is an excellent second wall of defense against wind driven rain and seepage due to ice damming.

#### Benefits

- Offers a skid resistant, sand surface
- Allows for easy installation and handling as a result of silicone treated split back release film
- Provides high temperature stability
- May be installed directly to concrete, plywood, wood composition board and gypsum
- Self seals around nails
- May be used in new construction or re-roofing
- Offers greater tear resistance than traditional felt underlayment
- Provides protection for critical areas such as rakes, eaves, valleys, flashings, hips, ridges, dormers and skylights
- Provides excellent low temperature flexibility



#### Specifications

<b>Reference ASTM</b>	1970
<b>Thickness, min</b>	55 mils
<b>Maximum Load, min</b>	MD=35 CD=35
<b>Elongation at Break, min</b>	30%
<b>Adhesion to Plywood @ 77 °F min</b>	30.0 lbf/ft
<b>Thermal Stability, max</b>	0.05
<b>Flexibility Temperature, @ -20 °F min</b>	pass
<b>Sealability around nail</b>	pass
<b>Water Proof Integrity after Low Temp. Flex</b>	pass
<b>Waterproof Integrity of lap Seam</b>	pass
<b>Slip Resistance</b>	pass
<b>Rolls per Pallet</b>	25
<b>Roll Weight</b>	68 lbs ± 2lbs
<b>Roll Diameter</b>	7.5 in.
<b>Square feet</b>	200