

STANDARD PHYSICAL CHARACTERISTICS AND SPECIFICATIONS
FOR ALL WOODFIBER INSULATION SYSTEMS**Cant and Tapered edge strip****DESCRIPTION:**

ALL MID-STATES WOODFIBER CANT STRIP AND TAPERED EDGE STRIP IS FABRICATED IN 48" STRIPS, FROM HIGH QUALITY, REGULAR DENSITY FIBERBOARD.

CANT STRIP:

MSA CANT IS AVAILABLE IN FIVE STANDARD SIZES TO ACCOMMODATE A WIDE VARIETY OF JOB REQUIREMENTS AND SPECIAL CONDITIONS. ALL MSA CANT IS CUT ON A 45° ANGLE TO INSURE A SMOOTH, STABLE TRANSITION FROM THE HORIZONTAL TO THE VERTICAL SURFACE.

TAPERED EDGE STRIP:

MSA EDGE STRIPS ARE CUT IN A WIDE VARIETY OF STANDARD SIZES RANGING FROM 1/2" X 6" TO 2" X 24". SPECIAL SIZES UP TO 3" X 24" ARE AVAILABLE UPON REQUEST.

SPECIFICATION:

MID-STATES FIBERBOARD CANT STRIP AND TAPERED EDGE STRIP IS FACTORY FABRICATED FROM ROOF INSULATION MEETING THE STANDARDS OF ASTM C208.

AVAILABILITY:

A COMPLETE INVENTORY OF POPULAR SIZES AND INSULATION TYPES ARE ALWAYS ON HAND FOR IMMEDIATE SHIPMENT. WE ALSO MAINTAIN A LARGE SUPPLY OF RAW MATERIALS TO INSURE QUICK TURNAROUND ON SPECIAL CUT ORDERS. THE UNIQUE ABILITY TO SHIP THESE QUALITY MATERIALS IN COMBINATION WITH OUR OTHER ASPHALT AND ROLL PRODUCTS, MAKES MID-STATES THE ECONOMICAL CHOICE FOR TODAY'S DISTRIBUTION NEEDS.

Tapered Insulation Systems**DESCRIPTION:**

MID-STATES TAPERED INSULATION IS USED IN A WIDE VARIETY OF BUR AND SINGLE PLY ROOFING APPLICATIONS TO HELP CREATE POSITIVE DRAINAGE AND PREVENT PONDING WATER. WHILE 1/2", 1/4" AND 1/8" SLOPES ARE STANDARD, SPECIAL INCLINES AND PANEL CONFIGURATIONS ARE ALSO AVAILABLE. MID-STATES TAPERED INSULATION SYSTEMS ARE AVAILABLE FOR MOST WARRANTED PROJECTS. PROFESSIONAL ESTIMATING SERVICES AND COMPUTER GENERATED SHOP DRAWINGS ARE PROVIDED ON ALL PROJECTS REGARDLESS OF SIZE.

SPECIFICATION:

MID-STATE'S TAPERED ROOF INSULATION IS FACTORY FABRICATED FROM QUALITY FIBERBOARD MEETING ASTM C208

SHIPPING:

A LARGE INVENTORY OF POPULAR SIZES ARE MAINTAINED IN STOCK TO INSURE TIMELY DELIVERIES TO YOUR WAREHOUSE OR JOB SITE. SYSTEMS ARE TYPICALLY SHIPPED IN FULL OR MIXED TRUCKS WITH VARIOUS COMBINATIONS OF OTHER MSA PRODUCTS SUCH AS ROLLS OR ASPHALT.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	METHOD	VALUE
WATER ABSORPTION	ASTM C209	10% VOLUME MAX.
WEIGHT SQ. FT.		1" THICK 1.6 LB.
COMPRESSION RESISTANCE		5% @ 24-40 PSI
LINEAR EXPANSION	ASTM C209	.05% MAX.
DRY DENSITY (LB./CU. FT.)	ASTM C209	17.5

THE SPECIFICATIONS COVERED ON THIS SUBMITTAL INCLUDE WOODFIBER USED FOR THE MANUFACTURING OF ALL MID-STATES CANT STRIP, TAPERED EDGE STRIP AND TAPERED INSULATION SYSTEMS.